



JP-8 MIL DTL-83133J 40021

EXISTENT GUM (WASHED) MG/100ML	7.0, MAX.	ASTM D381
PARTICULATE MATTER, MG/L	1, MAX.	ASTM D5452
FILTRATION TIME, MIN.	15, MAX.	ASTM D5452
FSII, VOL%	0.07 – 0.10	ASTM D5006
MICRO SEPAROMETER RATING	70, MIN	ASTM D3948
PARTICULATE COUNTING >4UM, PARTICLES/100ML	REPORT	IP 564
PARTICULATE COUNTING >6UM, PARTICLES/100ML	REPORT	IP 564
PARTICULATE COUNTING >14UM, PARTICLES/100ML	REPORT	IP 564
PARTICULATE COUNTING >21UM, PARTICLES/100ML	REPORT	IP 564
PARTICULATE COUNTING >25UM, PARTICLES/100ML	REPORT	IP 564
WATER RXN INTERFACE RATING	1B, MAX.	ASTM D1094
CORROSION INHIBITOR, PTB	6.0 – 8.4	
ANTIOXIDANT, PTB	3.2 – 8.4	
WATER CONTENT, VOL%	REPORT	ASTM E1064

Note: This information is offered for your consideration, investigation and verification. It should not be construed as a warranty or guaranty.

rethink_refine_resolve

Follow us on:



Office: 248_541_3824
Fax: 248_541_8970

821 Wanda Avenue
Ferndale, MI 48220

gageproducts.com