

<u>TEST</u>	<u>SPECIFICATION</u>	<u>METHOD</u>
RON	95.0-98.0	ASTM D2699
MON	85.0-89.0	ASTM D2700
OCTANE RATING	90.0-92.0	(R+M)/2
OCTANE SENSITIVITY	REPORT	R-M
DRIVEABILITY INDEX	REPORT	ASTM D4814
SULFUR CONTENT, PPM	10.0, MAX.	ASTM D5453
PHOSPHOROUS CONTENT, MG/L	1.30, MAX.	ASTM D3231
LEAD CONTENT, MG/L	5.00, MAX.	ASTM D3237
COPPER CORROSION	1A, MAX.	ASTM D130
BENZENE, VOL%	1.00, MAX.	ASTM D5580
EXISTENT GUM (WASHED), MG/100ML	4.00, MAX.	ASTM D381
UNWASHED GUMS, MG/100ML	REPORT	ASTM D381
OXIDATION STABILITY, MIN.	480, MIN.	ASTM D525
AROMATICS, VOL. %	25.0-32.0	ASTM D1319
OLEFINS, VOL. %	6.0-13.0	ASTM D1319
SATURATES, VOL. %	REPORT	ASTM D1319
HYDROGEN CONTENT, WT%	REPORT	ASTM D5291
CARBON CONTENT, WT%	REPORT	ASTM D5291
OXYGEN CONTENT, WT%	3.40-3.70	ASTM D5291
C/H RATIO, WT/WT	REPORT	CALCULATED
H/C RATIO, MOLE/MOLE	REPORT	CALCULATED
O/C RATIO, MOLE/MOLE	REPORT	CALCULATED
DISTILLATION, IBP, °C	REPORT	ASTM D86
DISTILLATION, 5%, °C	REPORT	ASTM D86
DISTILLATION, 10%, °C	REPORT	ASTM D86
DISTILLATION, 20%, °C	REPORT	ASTM D86
DISTILLATION, 30%, °C	REPORT	ASTM D86
DISTILLATION, 40%, °C	REPORT	ASTM D86
DISTILLATION, 50%, °C	REPORT	ASTM D86
DISTILLATION, 60%, °C	REPORT	ASTM D86
DISTILLATION, 70%, °C	REPORT	ASTM D86
DISTILLATION, 80%, °C	REPORT	ASTM D86
DISTILLATION, 90%, °C	REPORT	ASTM D86
DISTILLATION, 95%, °C	REPORT	ASTM D86

Note: This information is offered for your consideration, investigation and verification. It should not be construed as a warranty or guaranty.

rethink_refine_resolve

Follow us on:



Office: 248_541_3824
Fax: 248_541_8970

821 Wanda Avenue
Ferndale, MI 48220

gageproducts.com



Euro VI Cert Gasoline 41159

DISTILLATION, DP, °C	170.0-195.0	ASTM D86
RECOVERY	REPORT	ASTM D86
RESIDUE	2.0, MAX.	ASTM D86
LOSS	REPORT	ASTM D86
%EVAPORATED, @ 70 °C, VOL%	34.0-36.0	ASTM D86
% EVAPORATED @ 100 °C, VOL. %	54.0-62.0	ASTM D86
% EVAPORATED @ 150 °C, VOL. %	86.0-94.0	ASTM D86
RVP @ 100°F, PSI	8.13-8.71	ASTM D5191
API GRAVITY	REPORT	ASTM D4052
DENSITY @ 15°C, G/CC	0.743-0.756	ASTM D4052
ETHANOL CONTENT, VOL%	9.00-10.00	ASTM D4815
MTBE CONTENT, VOL%	NONE	ASTM D4815
ETBE CONTENT, VOL%	NONE	ASTM D4815
METHANOL CONTENT, VOL%	0.00-0.00	ASTM D4815
DEPOSIT CONTROL ADDITIVE	Y/N	CALCUALTED
APPEARANCE	PASS	VISUAL
COLOR	CLEAR	VISUAL
WATER CONTENT, WT%	0.05, MAX.	ASTM E1064

Note: This information is offered for your consideration, investigation and verification. It should not be construed as a warranty or guaranty.

rethink_refine_resolve

Office: 248_541_3824
Fax: 248_541_8970

821 Wanda Avenue
Ferndale, MI 48220

Follow us on:



gageproducts.com