

## Product Description

- High performance proven purge solvent designed to remove solvent borne paint
- Designed to maximize efficiency and minimize waste
- Standardized blends reduce variability and drive cost from the system while remaining sustainable
- All blends have high active solvent content leading to less solvent required during color change
- The results are the cleanest, most efficient and fastest color change possible along with a reduction in process variability and system costs

## General Application Instructions

- Efficient at removing wet and semi-dry paint from solventborne paint applicators and equipment
- Provides the “green” opportunity of the Gage Remanufactured Solvent program
- Demonstrated capability in reducing defects and foreign contamination on paint surfaces
- Utilize proper PPE and refer to MSDS when handling purge solvents
- Compatible for use with solventborne paints and substrates of all major paint suppliers
- Can offer significant VOC reductions through implementation of the Gage closed loop process

## Physical Properties

PURGE SOLVENT BLENDS														
Product Code	30170	31305	31311	31317	31700	31720	31867	31868	31872	31881	31915	31917	31920	31925
Virgin or Reclaim	Reclaim	Reclaim	Reclaim	Reclaim	Reclaim	Reclaim	Reclaim	Reclaim	Virgin	Reclaim	Virgin	Virgin	Reclaim	Reclaim
VOC, lb/gal	7.25	7.25	7.23	7.25	7.27	7.34	4.20	5.71	4.20	6.77	4.20	4.80	5.71	4.90
HAPS, wt%	<40	<40	<42	<35	<32	<22	<40	<40	<1	<8	<1	<30	<9	<8
Flash Point, °F	61	61	62	62	68	68	-4	-4	-4	19	-4	-4	-4	-4
Water, wt%	<0.1	<0.1	<0.1	<0.1	<0.1	<0.2	<0.5	<0.5	<1.0	<0.5	<0.2	<0.5	<0.2	<0.2
Resistivity, MΩ	>1	>1	>1	>1	>1	>1	<1	<1	<1	>0.3	>0.3	<0.3	>0.3	>0.1
Specific Gravity @ 60°F	0.87	0.87	0.87	0.87	0.87	0.88	0.84	0.86	0.84	0.79	0.84	0.82	0.86	0.84
Weight/gal	7.25	7.25	7.24	7.25	7.27	7.34	7.02	7.13	7.00	6.80	7.00	6.88	7.15	7.03

**Note:** As with all chemicals, proper safety procedures should be adhered to at all times. Please review product Material Safety Data Sheet prior to working with any chemicals. Please contact your Gage Products Company representative for process specific application instructions.

The technical information and suggestions for use made herein are based on Gage Products Company’s research and experience and are believed to be reliable. Such information and suggestions however, do not constitute a warranty.

Since Gage Products Company has no control over the conditions under which the product is transported, stored, handled, and/or applied, buyers must determine for themselves, by preliminary tests or otherwise, the suitability of the product for their purposes.