

HYDROPURGE™

PRODUCT DESCRIPTION

- ◆ Reduced solvent blend formulated to purge waterborne paint from paint applicators.
- ◆ Contains 3.8 lb/gl. VOC.
- ◆ Translucent, amber liquid as supplied.
- ◆ Ultra low VOC content when diluted for use.

PHYSICAL PROPERTIES

- ◆ Appearance: Clear liquid
- ◆ Density: 8.15 lb/gl
- ◆ VOC Content (EPA Method 24): 3.8 lb/gl
- ◆ pH: 10.75 - 11.75
- ◆ Flash Point (PMCC): > 212°F
- ◆ Do not allow to freeze

PRODUCT FEATURES

- ◆ Effective at removing wet and semi-dry paint from waterborne paint applicators and equipment.
- ◆ Designed to be diluted to a 5-15% concentration in RO water for maximum effectiveness.
- ◆ Better performance can be achieved by heating the product from 90 to 130 F.
- ◆ When diluted, product becomes cloudy in appearance.
- ◆ The diluted product should be agitated at all times to prevent separation into two phases.
- ◆ Compatible with polyethylene, polypropylene, Teflon, and EPDM.
- ◆ Incompatible with aluminum, galvanized, zinc, copper, or brass components.
- ◆ Incompatible with natural rubber and Buna-N.



Note: As with all chemicals, proper safety procedures should be adhered to at all times. Please review product Safety Data Sheet prior to working with any chemicals. Please contact your Gage Products Company representative for process specific application instructions.

The technical information and suggestions for use made herein are based on Gage Products Company's research and experience and are believed to be reliable. Such information and suggestions however, do not constitute a warranty. Information provided in this document is not to be used for regulatory and/or environmental reporting purposes.

Since Gage Products Company has no control over the conditions under which the product is transported, stored, handled, and/or applied, buyers must determine for themselves, by preliminary tests or otherwise, the suitability of the product for their purposes.