

Gage Products Company Technical Data Sheet

Page: 1

Date Printed: 12/17/19 at 2:15 PM

SAE AMS2629E 42433-55C

Test	Method	UOM	Specification
JET A FUEL CONTENT	Calculated	VOL%	72.8 - 74.8
ACID NUMBER	ASTM D3242	MG KOH/G	0.100, MAX
AROMATIC CONTENT	ASTM D1319	VOL.%	24.0 - 26.0
OLEFIN CONTENT	ASTM D1319	VOL.%	REPORT
SATURATE CONTENT	ASTM D1319	VOL.%	REPORT
DISTILLATION, IBP	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 5%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 10%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 20%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 30%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 40%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 50%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 60%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 70%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 80%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 90%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, 95%	ASTM D86	DEG C (DEG F)	REPORT
DISTILLATION, DRY POINT	ASTM D86	DEG C (DEG F)	REPORT
RECOVERY	ASTM D86	VOL.%	REPORT
LOSS	ASTM D86	VOL.%	REPORT
RESIDUE	ASTM D86	VOL.%	REPORT
SPECIFIC GRAVITY @ 60.0 F	ASTM D4052		REPORT
DENSITY @ 15.56 C	ASTM D4052	G/CC	REPORT
API GRAVITY @ 60 F	ASTM D4052		REPORT
DENSITY @ 15.00 C	ASTM D4052	KG/L	REPORT
FSII	ASTM D5006	VOL%.	0.09 - 0.13
COPPER CORROSION	ASTM D130	COPPER CORR.	1, MAX.
WATER RXN INTERFACE RATING	ASTM D1094		1B, MAX.
CHANGE IN WATER LAYER	ASTM D1094	ML	2ML, MAX.
SULFUR AS DI-TERT-BUTYL-DISULFIDE	ASTM D2622	WT%	0.40 - 0.44
MERCAPTAN CONTENT	ASTM D3227	WT%	0.0045 - 0.0055
COLOR, SAYBOLT	ASTM D156		25, MIN.

NOTE: This information is offered for your consideration, investigation, and verification. It should not be construed as a warranty or guaranty.

Office: 248_541_3824

Fax: 248_541_8970



Gage Products Company Technical Data Sheet

Page: 2

Date Printed: 12/17/19 at 2:15 PM

SAE AMS2629E 42433-55C

COPPER CONTENT	ICP-MS	MG/KG	0.05, MAX.	1
CADMIUM CONTENT	ICP-MS	MG/KG	0.05, MAX	

NOTE: This information is offered for your consideration, investigation, and verification. It should not be construed as a warranty or guaranty.

Office: 248_541_3824

Fax: 248_541_8970