



# Gage Products Company Technical Data Sheet

Page: 1

Date Printed: 12/16/19 at 9:41 PM

Euro IV Diesel  
42652-55F

Test	Method	UOM	Specification
CETANE NUMBER	ASTM D613	CETANE NO.	52.0 - 54.0
SULFUR CONTENT	ASTM D5453	PPM	10, MAX.
POLYNUCLEAR AROMATIC CONTENT	ASTM D5186	WT. %	3.00 - 6.00
DENSITY @ 15.00 C	ASTM D4052	KG/M <sup>3</sup>	833.0 - 837.0
DISTILLATION, IBP	ASTM D86	DEG C	REPORT
DISTILLATION, 10%	ASTM D86	DEG C	REPORT
DISTILLATION, 20%	ASTM D86	DEG C	REPORT
DISTILLATION, 30%	ASTM D86	DEG C	REPORT
DISTILLATION, 40%	ASTM D86	DEG C	REPORT
DISTILLATION, 50%	ASTM D86	DEG C	245, MIN.
DISTILLATION, 60%	ASTM D86	DEG C	REPORT
DISTILLATION, 70%	ASTM D86	DEG C	REPORT
DISTILLATION, 80%	ASTM D86	DEG C	REPORT
DISTILLATION, 90%	ASTM D86	DEG C	REPORT
DISTILLATION, 95%	ASTM D86	DEG C (DEG F)	345.0 - 350.0 (653.0 - 662.0)
DISTILLATION, DP	ASTM D86	DEG C	370, MAX.
PMCC FLASHPOINT	ASTM D93	DEG C	55, MIN.
KIN. VISCOSITY @ 40C	ASTM D445	CST	2.30 - 3.30
CFPP	ASTM D6371	DEG C	-5, MAX.

**NOTE: This information is offered for your consideration, investigation, and verification. It should not be construed as a warranty or guaranty.**

rethink\_refine\_resolve®

Office: 248\_541\_3824  
Fax: 248\_541\_8970

821 Wanda Avenue  
Ferndale, MI 48220

gageproducts.com