



Gage Products Company Technical Data Sheet

Page: 1

Date Printed: 12/16/19 at 9:35 PM

ULSD B20 Biodiesel
42826-55F

Test	Method	UOM	Specification
SME BIODIESEL	GAGE-GC2	VOL. %	18.00 - 22.00
SULFUR CONTENT	ASTM D5453	PPM	0.0 - 15.0
SPECIFIC GRAVITY @ 60.0 F	ASTM D4052		REPORT
DENSITY @ 15.56 C	ASTM D4052	G/CC	REPORT
RANCIMAT NUMBER (OXID STAB BXX BLEND)	EN 15751	HOURS	6, MIN
ACID NUMBER	ASTM D974	MG KOH/G	0.30 MAX.
WATER CONTENT	ASTM E1064	MG/KG	200.0, MAX
PARTICULATE MATTER	ASTM D5452	MG/L	24, MAX.
CLOUD POINT	ASTM D2500	DEG C	REPORT
POUR POINT	ASTM D97	DEG C	REPORT
CFPP	ASTM D6371	DEG C	REPORT
ODOR TEST	ASTM D1296	PASS	PASS
OTHER ADDITIVES		Y/N	Y/N
APPEARANCE	VISUAL INSPECTION (C, B, F)	PASS	Y/N

NOTE: This information is offered for your consideration, investigation, and verification. It should not be construed as a warranty or guaranty.

rethink_refine_resolve®

Office: 248_541_3824
Fax: 248_541_8970

821 Wanda Avenue
Ferndale, MI 48220

gageproducts.com